


LED recessed downlight, IP44  
**Artikel-Nr. 12127153**



LED recessed downlight, IP44, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Die-cast aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44\*, Protection class: (EN 61140) III, Voltage: 12V, Power: 5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 400lm, Colour temperature: 2.900 K, Light colour : White, Beam angle: 60°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 12127153         |
| Stand:      | 25.10.2021 23:08 |

|                                    |                                     |
|------------------------------------|-------------------------------------|
| Colour temperature                 | 2900 K                              |
| Colour                             | Nickel                              |
| Beam angle                         | 60 °                                |
| Amount of light sources / fittings | 1 Qty                               |
| Material                           | Die-cast aluminium / Plastic        |
| Power                              | 5 W                                 |
| Lamp                               | LED                                 |
| scope of delivery                  | Including 2,000 mm connecting cable |
| Colour rendering                   | CRI 85                              |

|                      |                             |
|----------------------|-----------------------------|
| Control              | Dimming depending on driver |
| Outer diameter       | 75 mm                       |
| Built-in diameter    | 68 mm                       |
| Installation depth   | 14 mm                       |
| Voltage              | 12V                         |
| Degree of protection | IP44*                       |
| Protection class     | III                         |
| Adjustability        | Not adjustable              |
| Aufbauhöhe           | 3 mm                        |
| Circuit type         | Parallel conduction         |