


LED recessed downlight, IP44

Artikel-Nr. 12128153

LED recessed downlight, IP44, nickel, square. In a compact design, for installation in tool-less rapid assembly systems. Lamp optimized for installation in furniture and wood-based materials. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Die-cast aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Voltage: 12V, Power: 5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 400lm, Colour temperature: 2.900 K, Light colour : White, Beam angle: 60°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12128153		
Stand:	26.10.2021 02:27		
Colour temperature	2900 K	Control	Dimming depending on driver
Colour	Nickel	Built-in diameter	68 mm
Length	75 mm	Installation depth	14 mm
Beam angle	60 °	Voltage	12V
Amount of light sources / fittings	1 Qty	Degree of protection	IP44*
Material	Die-cast aluminium / Plastic	Protection class	III
Power	5 W	Adjustability	Not adjustable
Lamp	LED	Length	75 mm
scope of delivery	Including 2,000 mm connecting cable	Width	75 mm
Colour rendering	CRI 85	Aufbauhöhe	3 mm
		Circuit type	Parallel conduction