

Recessed housing, rectangular, flush, 2-x, recessed with module holders, pivoted



Recessed housing, rectangular, flush, 2-x, recessed with module holders, pivoted, black, rectangular. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, control: Other.

Artikel-Nr.	45025 180		
Stand:	20.07.2021 13:20		
Colour	Black	Built-in width	1 60 mm
Length	175 mm	Built-in length	81 mm
Amount of light sources / fittings	2 Qty	Degree of protection	IP20
Material	Aluminium	Protection class	III
Lamp holder	Without fitting	Circlip	Without circlip
Power	2 x LED, max. 14 W	Length	175 mm
Lamp	Other	Width	92 mm
Shipping	Incl. module brackets, recessed, pivoted	Height	2.5 mm
control	Other	Swivel angle	20 °