


LED recessed panel FLAT30, TunableWhite

Artikel-Nr. 12437684

LED recessed panel FLAT30, TunableWhite, white, round. In a compact design, for installation in tool-less rapid assembly systems. Luminous flux: 2700K: 550lm, 5700K: 760lm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 24V, Power: 20W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 550lm, Colour temperature: from 2.700 K up to 5.700 K, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12437684
Stand:	25.10.2021 22:43

Colour temperature	2700 K - 5700 K
Colour	White
Beam angle	120 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	20 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver
Outer diameter	200 mm

Built-in diameter	180 mm
Installation depth	30 mm
Voltage	24V
Luminous flux	550 lm
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	5 mm
Circuit type	Parallel conduction