



QualityFlex Select flex lighting 5 m, CRI > 90, 9,6 W / m, IP00
Artikel-Nr. 15202027



QualityFlex Select flex lighting 5 m, CRI > 90, 9,6 W / m, IP00, white, 2.700K, CRI > 90. LED flex lighting for decorative, technical as well as efficient lighting of light coves, linear applications and backlighting, basic or general lighting of rooms, architectural applications and for areas where high illumination is required, such as indirect or direct lighting, luminous ceilings, gastronomy lighting and much more. Länge: 5000.0 mm Lampenleistung je Meter: 9.6 W/m, Lichtstrom je Meter: 770.0 lm/m, Schutzart raumseitig: IP00, Schutzklasse: III, Spannung: 24V DC, Abstrahlwinkel: 120.0 °, 120 LEDs pro Meter, Chip-Abstand (Short Pitch) : 8,3mm. Zur Individuellen Anwendung kann die LED-Flexplatine alle 50 mm eingekürzt werden. Die maximale Systemlänge von 5.000mm darf mit einer Einspeisung nicht überschritten werden. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	15202027
Stand:	06.12.2021 18:01

Colour temperature	2700 K
Light colour	White
Luminous flux per meter	770 lm/m
Power	48 W
Lamp power per meter	9,6 W/m
Power fix	48 W
Beam angle	120 °
Length	5,000 mm
Width	8 mm
Aufbauhöhe	1.4 mm
Length of individual sections	50 mm
Degree of protection	IP00

Protection class	III
McAdam-Step	McAdam-Step 5
Short Pitch	8.3 mm
Number of lamps per meter	120 Qty
Voltage	24V
Voltage type	DC
Ambient temperature	-10 °C bis +40 °C
Control	Dimming depending on driver
Circuit type	Parallel conduction
Length of the connection line	350 mm
Maximum module length	5,000 mm