

Recessed housing oval, flush, 2-x, with module holders flush, rigid
Artikel-Nr. 45021550



Recessed housing oval, flush, 2-x, with module holders flush, rigid, white / black, other. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Installation diameter: 2x82 mm Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, control: Other.

Artikel-Nr.	45021550
Stand:	19.07.2021 19:47

Colour	White / Black
Length	175 mm
Amount of light sources / fittings	2 Qty
Material	Aluminium
Lamp holder	Without fitting
Power	2 x LED, max. 14 W
Lamp	Other
Shipping	Incl. module brackets flush, rigid, IP44

control	Other
Built-in width	164 mm
Built-in length	82 mm
Degree of protection	IP20
Protection class	III
Circlip	Without circlip
Length	175 mm
Width	92 mm
Height	2.5 mm