


LED recessed spot, dim2warm

**Artikel-Nr. 12492153**

recessed spot, nickel matt. In a compact design, for installation in tool-less rapid assembly systems. Wird die Leuchte gedimmt, verringert sich die Farbtemperatur. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 880lm, Colour temperature: from 3000 K to 1800 K, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver.

**Artikel-Nr.** 12492153  
**Stand:** 20.07.2021 22:01

Colour of light	3000 - 1800 K
Colour	Nickel
Length	110 mm
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	12 W
Lamp	LED
Colour rendering	CRI > 80
control	Dimming depending on driver

Built-in diameter	95 mm
Installation depth	60 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Length	110 mm
Width	110 mm
Swivel angle	15 °
Circuit type	Series conduction