


LED recessed panel FLAT30
Artikel-Nr. 12217683



LED recessed panel FLAT30, silver, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 24V, Power: 16W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.040lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12217683
Stand:	25.10.2021 21:05

Colour temperature	3000 K
Colour	Silver
Beam angle	120 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	16 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	200 mm
Built-in diameter	180 mm
Installation depth	30 mm
Voltage	24V
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	5 mm
Circuit type	Parallel conduction