


LED converter 350 mA, trailing-edge phase dimmable
Artikel-Nr. 17640020



LED converter 350 mA, trailing-edge phase dimmable, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 2.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 10W, Control: Trailing-edge phase.

Artikel-Nr.	17640020
Stand:	06.12.2021 15:43

version	Plug&Play + Anschlussbox	Voltage	230V AC 50Hz
Power	4,2-10 W	Current	350 mA
Current	350 mA	Circuit type	Series conduction
Control	Trailing-edge phase	Degree of protection	IP20
Material	Plastic	Protection class	II
Enviroment temprature (ta)	-25 °C bis +45 °C	Voltage type	DC
Measure point (tc)	max. +70 °C	Length	102 mm
Power	4,2-10 W	Width	38 mm
Dimensions	L 102 x B 38 x H 21 mm	Aufbauhöhe	21 mm
Input voltage	AC: 220-240 V		
scope of delivery	Plug&Play version with 110 mm P&P output cable		