


LED converter 350 mA, trailing-edge phase dimmable
Artikel-Nr. 17663020



LED converter 350 mA, trailing-edge phase dimmable, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 7W, dimmable: Yes, Control: Trailing-edge phase.

Artikel-Nr.	17663020
Stand:	06.12.2021 18:41

version	Plug&Play + Anschlussbox
Power	2,8-7 W
Current	350 mA
Output power	2,8-7 W
Control	Trailing-edge phase
Material	Plastic
Enviroment temprature (ta)	0°C up to 40°C
Measure point (tc)	max. +80 °C
Power	2,8-7 W
Dimensions	L 110 x B 50 x H 19 mm
Input voltage	AC: 198-264 V

scope of delivery	Plug&Play version with 110 mm P&P output cable
Voltage	230V AC 50Hz
Current	350 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Length	110 mm
Width	50 mm
Aufbauhöhe	19 mm