


LED converter 350 mA, on/off
Artikel-Nr. 17662020



LED converter 350 mA, on/off, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 350 mA, Voltage: 230V AC 50Hz, Power: 7.2W, dimmable: No, Control: on/off.

Artikel-Nr.	17662020
Stand:	06.12.2021 10:17

version	Plug&Play + Anschlussbox
Power	1-7,2 W
Current	350 mA
Control	on/off
Material	Plastic
Enviroment temprature (ta)	-20°C up to +50°C
Measure point (tc)	max. +75 °C
Power	1-7,2 W
Dimensions	L 68 x B 35 x H 21 mm
Input voltage	AC: 220-240 V

scope of delivery	Plug&Play version with 110 mm P&P output cable
Voltage	230V AC 50Hz
Current	350 mA
Degree of protection	IP20
Protection class	II
Length	68 mm
Width	35 mm
Aufbauhöhe	21 mm

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.