


LED converter 700 mA, on/off
Artikel-Nr. 17723020



LED converter 700 mA, on/off, This converter is equipped with safety devices which protect it against overvoltage, short-circuit as well as thermal and electric overloads. The input and output terminals are suitable for cables with a cross-section of up to 1.5 mm². . Material: Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Current: 700 mA, Voltage: 230V AC 50Hz , Power: 31W, Control: on/off.

Artikel-Nr.	17723020
Stand:	06.12.2021 16:41

version	Plug&Play + Anschlussbox
Power	1,4-31 W
Current	700 mA
Control	on/off
Material	Plastic
Environment temperature (ta)	-25 °C bis +40 °C
Measure point (tc)	max. +80 °C
Power	1,4 - 31 W
Dimensions	L 146,5 x B 43,5 x H 30 mm
Input voltage	AC: 220-240 V, DC: 170-280 V
scope of delivery	Plug&Play version with 110 mm P&P output cable

Voltage	230V AC 50Hz
Current	700 mA
Circuit type	Series conduction
Degree of protection	IP20
Protection class	II
Voltage type	DC
Length	146.5 mm
Width	43.5 mm
Aufbauhöhe	30 mm