


LED light point, IP44
Artikel-Nr. 12071253



LED light point, IP44, alu, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 350 mA, Power: 1.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 70lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 30°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12071253
Stand:	25.10.2021 21:58

Colour temperature	3000 K
Colour	Alu
Beam angle	30 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	1,2 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	32.5 mm
Built-in diameter	27 mm
Installation depth	17 mm
Current	350 mA
Degree of protection	IP44 *
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	3.5 mm
Circuit type	Series conduction