


LED recessed panel FLAT30

Artikel-Nr. 12217684

LED recessed panel FLAT30, silver, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 24V, Power: 16W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.080lm, Colour temperature: 4.000 K, Light colour : White, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr. 12217684
Stand: 26.10.2021 01:36

| | |
|------------------------------------|-----------------------------|
| Colour temperature | 4000 K |
| Colour | Silver |
| Beam angle | 120 ° |
| Amount of light sources / fittings | 1 Qty |
| Material | Aluminium / Plastic |
| Power | 16 W |
| Lamp | LED |
| Colour rendering | CRI > 80 |
| Control | Dimming depending on driver |

| | |
|----------------------|---------------------|
| Outer diameter | 200 mm |
| Built-in diameter | 180 mm |
| Installation depth | 30 mm |
| Voltage | 24V |
| Degree of protection | IP20 |
| Protection class | III |
| Adjustability | Not adjustable |
| Aufbauhöhe | 5 mm |
| Circuit type | Parallel conduction |