

Surface mounted housing round, recessed, with module bracket recessed, pivoted



Surface mounted housing round, recessed, with module bracket recessed, pivoted, black / white, round. Surface mounting, Ceiling-mounted. All Brumberg MR16 LED modules can be used for the surface mounted unit M1 up to the specified power. The LED module, the converter or the power supply unit and, if applicable, the control are not included in the scope of delivery of the surface mounted unit. We will be happy to answer any questions you may have about the selection of converters that fit into the housing. Important: when using 24 V LED modules, the power supply unit and the control must always be installed on site outside the housing. Lamp holder: Without fitting, Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 8W, Amount of light sources / fittings: 1.0 Qty, Adjustability: Pivoted, With control gear: No, Control: Other.

<b>Artikel-Nr.</b>	<b>45102560</b>
<b>Stand:</b>	07.12.2021 10:26

Colour	Black / White
Amount of light sources / fittings	1 Qty
Control	Other
Outer diameter	90 mm
Material	Aluminium
Aufbauhöhe	115 mm
Lamp holder	Without fitting
Power	LED, max. 8 W
Lamp	Other

scope of delivery	Incl. module holder recessed, pivoted
Degree of protection	IP20
Protection class	III
Swivel angle	20 °
Circlip	Without circlip
Adjustability	Pivoted