


Recessed housing, rectangular, flush, 2-x, with flush module holders, pivoted

Artikel-Nr. 45023560



Recessed housing, rectangular, flush, 2-x, with flush module holders, pivoted, black / white, rectangular. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 2.0 Qty, With control gear: No, control: Other.

| | |
|--------------------|------------------|
| Artikel-Nr. | 45023560 |
| Stand: | 20.07.2021 05:07 |

| | |
|------------------------------------|--------------------------------------|
| Colour | Black / White |
| Length | 175 mm |
| Amount of light sources / fittings | 2 Qty |
| Material | Aluminium |
| Lamp holder | Without fitting |
| Power | 2 x LED, max. 14 W |
| Lamp | Other |
| Shipping | Incl. module brackets flush, pivoted |
| control | Other |

| | |
|----------------------|-----------------|
| Built-in width | 160 mm |
| Built-in length | 81 mm |
| Degree of protection | IP20 |
| Protection class | III |
| Circlip | Without circlip |
| Length | 175 mm |
| Width | 92 mm |
| Height | 2.5 mm |
| Swivel angle | 20 ° |