

Recessed housing, rectangular, flush, 3-x, with flush module holders, rigid
Artikel-Nr. 45027560



Recessed housing, rectangular, flush, 3-x, with flush module holders, rigid, black / white, rectangular. In a compact design, for installation in tool-less rapid assembly systems. All Brumberg MR16 LED modules can be used for the installation unit M1 up to the maximum specified power. The installation depth of the luminaire depends on the LED module used. The LED module is not included in the scope of delivery of the installation unit. Lamp holder: Without fitting, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Power: 14W, Amount of light sources / fittings: 3.0 Qty, With control gear: No, control: Other.

Artikel-Nr. 45027560			
Stand: 19.07.2021 17:10			
Colour	Black / White	control	Other
Length	260 mm	Built-in width	250 mm
Amount of light sources / fittings	3 Qty	Built-in length	81 mm
Material	Aluminium	Degree of protection	IP20
Lamp holder	Without fitting	Protection class	III
Power	3 x LED, max. 14 W	Circlip	Without circlip
Lamp	Other	Length	260 mm
Shipping	Incl. module brackets flush, rigid, IP44	Width	92 mm
		Height	2.5 mm