


LED pendant profile luminaire direct/indirect BIRO40
Artikel-Nr. 77334088



LED pendant profile luminaire direct/indirect BIRO40, black, rectangularLamp holder: LED, Mounting method: Suspended, Place of installation: Ceiling-mounted, Material: Aluminium / Acrylic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 94.9W, Luminous flux: 11.080lm, Colour temperature: from 2700 K up to 6500 K, Light colour : White, Beam angle: 80°, Adjustability: Not adjustable, With control gear: Yes.

Artikel-Nr.	77334088
Stand:	22.07.2021 02:43

control	DALI
Colour	Black
Colour of light	2700 K - 6500 K
Glare evaluation	UGR < 19
System efficiency	117 lm/W
Luminous flux	11,080 lm
Material cover	Microprismatic
Length	2264 mm
Colour rendering	CRI > 80
Beam angle	80 °

Material	Aluminium / Acrylic
Lamp holder	LED
Lamp	LED
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	I
Adjustability	Not adjustable
Width	40 mm
Height	75 mm
Circuit type	Parallel conduction
Pendulum length max.	1,500 mm