


LED recessed downlight set with indirect component, phase dimmable
Artikel-Nr. 39406073



LED recessed downlight set with indirect component, phase dimmable, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp with direct and indirect light component. Set including a converter for 230-V mains voltage, trailing-edge phase, dimensions of converter: L 125 x W 51 x H 20 mm Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 10.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 887lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 34°, Adjustability: Not adjustable, With control gear: Yes, dimmable: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39406073
Stand:	26.10.2021 04:16

Colour temperature	3000 K
Colour	White
Beam angle	34 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	10,5 W
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase

Outer diameter	110 mm
Built-in diameter	83 mm
Installation depth	80 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Aufbauhöhe	14 mm
Circuit type	Parallel conduction