


LED recessed downlight with indirect component
Artikel-Nr. 12406073



LED recessed downlight with indirect component, white, round. In a compact design, for installation in tool-less rapid assembly systems. Lamp with direct and indirect light component. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 10.5W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 887lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 45°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12406073
Stand:	25.10.2021 22:14

Colour temperature	3000 K
Colour	White
Beam angle	34 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	10,5 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Outer diameter	110 mm
Built-in diameter	83 mm
Installation depth	80 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Aufbauhöhe	14 mm
Circuit type	Series conduction