


LED recessed downlight CIRCLE, with all-round light gap
Artikel-Nr. 124 15 173



LED recessed downlight CIRCLE, with all-round light gap, white, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6.1W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 50°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	124 15 173
Stand:	26.10.2021 03:08

Colour temperature	3000 K
Colour	White
Beam angle	50 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Lamp holder	Plug&Play
Power	6,1 W
Lamp	LED
Colour rendering	CRI > 90

Control	Dimming depending on driver
Outer diameter	74 mm
Built-in diameter	68 mm
Installation depth	53 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction