


LED recessed spot set BB23, IP65, DALI dimmable incl. connection box  
**Artikel-Nr. 41484153**



LED recessed spot set BB23, IP65, DALI dimmable incl. connection box, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, DALI-2 dimmable, dimensions of converter: L 130 x W 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP65\*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 620lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Pivoted, With control gear: Yes, Control: DALI-2 .

|                                    |                     |
|------------------------------------|---------------------|
| Artikel-Nr.                        | 41484153            |
| Stand:                             | 26.10.2021 05:31    |
| Colour temperature                 | 3000 K              |
| Colour                             | Nickel              |
| Beam angle                         | 36 °                |
| Amount of light sources / fittings | 1 Qty               |
| Material                           | Aluminium / Plastic |
| Power                              | 7 W                 |
| Lamp                               | LED                 |
| Colour rendering                   | CRI > 80            |
| Control                            | DALI-2              |
| Outer diameter                     | 82 mm               |
| Built-in diameter                  | 68 mm               |
| Installation depth                 | 55 mm               |
| Voltage                            | 230V AC 50Hz        |
| Degree of protection               | IP65*               |
| Protection class                   | II                  |
| Adjustability                      | Pivoted             |
| Swivel angle                       | 15 °                |
| Circuit type                       | Parallel conduction |
| Suitable for through-wiring        | Yes                 |