



LED recessed downlight set BB20, IP65, on/off
Artikel-Nr. 38480153



LED recessed downlight set BB20, IP65, on/off, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, on/off switchable, dimensions of converter: L 68 x W 35 x H 21 mm . Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP65*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 620lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Not adjustable, With control gear: Yes, Control: on/off.

Artikel-Nr.	38480153
Stand:	26.10.2021 04:40

Colour temperature	3000 K
Colour	Nickel
Beam angle	36 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	on/off

Outer diameter	85 mm
Built-in diameter	68 mm
Installation depth	50 mm
Voltage	230V AC 50Hz
Degree of protection	IP65*
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction