


LED system downlight COUPLED, IP44, round
Artikel-Nr. 12630073



LED system downlight COUPLED, IP44, round, white, round. In a compact design, for installation in tool-less rapid assembly systems. Installation is only with plaster or installation frame 82030170 or 82032170 possible. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 500 mA, Power: 8.9W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 950lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 34°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12630073
Stand:	25.10.2021 21:42

Colour temperature	3000 K
Colour	White
Beam angle	34 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	8,9 W
Lamp	LED
Colour rendering	CRI > 90
Control	Dimming depending on driver

Outer diameter	68 mm
Installation depth	79 mm
Current	500 mA
Luminous flux	950 lm
Degree of protection	IP44 *
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction