


LED-Wandanbauleuchte, IP65
Artikel-Nr. 60127253



LED-Wandanbauleuchte, IP65, alu, rectangular. Surface mounting, Wall-mounted. Direct and indirect light emission. Mounting method: Surface mounting, Place of installation: Wall-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP65*, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 4.6W, Amount of light sources / fittings: 2.0 Qty, Colour temperature: 3.000 K, Beam angle: 50°, With control gear: Yes, Control: on/off.

Artikel-Nr.	60127253
Stand:	25.10.2021 19:48

Colour temperature	3000 K
Colour	Alu
Beam angle	50 °
Amount of light sources / fittings	2 Qty
Material	Aluminium / Glass
Power	2 x 4,6 W
Lamp	LED
scope of delivery	Incl. converter for connection to the 230-V mains voltage
Colour rendering	CRI > 90

Control	on/off
Voltage	230V AC 50Hz
Circuit type	Parallel conduction
Degree of protection	IP65*
Protection class	I
Voltage type	AC
Length	230 mm
Width	43 mm
Aufbauhöhe	90 mm
Dimensions	L x B x H: 230 x 90 mm

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.