



LED recessed spot set BB25, IP65, DALI dimmable incl. connection box
Artikel-Nr. 41488183



LED recessed spot set BB25, IP65, DALI dimmable incl. connection box, black, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, DALI-2 dimmable, dimensions of converter: L 130 x W 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP65*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 620lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 36°, Adjustability: Pivoted, With control gear: Yes, Control: DALI-2 .

Artikel-Nr.	41488183
Stand:	26.10.2021 03:41

Colour temperature	3000 K
Colour	Black
Beam angle	36 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	DALI-2
Outer diameter	82 mm

Built-in diameter	68 mm
Installation depth	55 mm
Voltage	230V AC 50Hz
Luminous flux	680 lm
Degree of protection	IP65*
Protection class	II
Adjustability	Pivoted
Swivel angle	15 °
Circuit type	Parallel conduction
Suitable for through-wiring	Yes