




LED recessed spot
Artikel-Nr. 12292153



LED recessed spot, nickel, square. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.080lm, Colour temperature: 2700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, control: Dimming depending on driver. This luminaire contains incorporated and non-exchangeable LED light sources.

Artikel-Nr.	12292153
Stand:	19.07.2021 09:44

Colour of light	2700 K
Colour	Nickel
Length	110 mm
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	12 W
Lamp	LED
Colour rendering	CRI > 80
control	Dimming depending on driver

Built-in diameter	95 mm
Installation depth	60 mm
Current	350 mA
Luminous flux	1,080 lm
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Length	110 mm
Width	110 mm
Swivel angle	15 °
Circuit type	Series conduction