


LED recessed downlight ALTERO, IP44
Artikel-Nr. 12036404



LED recessed downlight ALTERO, IP44, white / chrome, square. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP44*, Protection class: (EN 61140) III, Current: 500 mA, Power: 9.2W, Amount of light sources / fittings: 1 Qty, Luminous flux: 840lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 33°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.

Stand:

12036404

20.07.2021 14:47

Colour of light	4000 K	Built-in diameter	68 mm
Colour	White / Chrome	Installation depth	72 mm
Beam angle	33 °	Current	500 mA
Amount of light sources / fittings	1 Qty	Degree of protection	IP44 *
Material	Aluminium / Glass / Plastic	Protection class	III
Power	9,2 W	Adjustability	Not adjustable
Lamp	LED	Length	83 mm
Colour rendering	CRI > 80	Width	83 mm
control	Dimming depending on driver	Circuit type	Series conduction