


LED recessed spot
Artikel-Nr. 12374643



LED recessed spot, titanium, square. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 3W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 290lm, Colour temperature: 2.700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12374643
Stand:	26.10.2021 01:31

Colour temperature	2700 K	Installation depth	50 mm
Colour	Titanium	Current	350 mA
Length	82 mm	Degree of protection	IP20
Beam angle	38 °	Protection class	III
Amount of light sources / fittings	1 Qty	Circlip	Without circlip
Material	Aluminium / Glass	Adjustability	Pivoted
Lamp holder	Plug&Play	Length	82 mm
Lamp	LED	Width	82 mm
Colour rendering	CRI > 80	Swivel angle	20 °
Control	Dimming depending on driver	Circuit type	Series conduction
Built-in diameter	68 mm		

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.