


LED recessed spot ARUN, 2-x
Artikel-Nr. 12613173



LED recessed spot ARUN, 2-x, white, oval. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12.2W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.600lm, Colour temperature: 3.000 K, Beam angle: 29°, Adjustability: Rotable and pivoted, Control: Dimming depending on driver.

Artikel-Nr.	12613173
Stand:	26.10.2021 01:48

Colour temperature	3000 K
Colour	White
Length	92 mm
Beam angle	29 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	2 x 12,2 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver

Built-in width	174 mm
Built-in length	83 mm
Installation depth	95 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Rotable and pivoted
Rotation angle	355 °
Swivel angle	30 °
Circuit type	Series conduction