




LED recessed downlight BOWL
Artikel-Nr. 12529073



LED recessed downlight BOWL, white, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / PMMA, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 700 mA, Power: 30W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 2.500lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 97°, Adjustability: Not adjustable, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12529073
Stand:	25.10.2021 22:48
Colour temperature	3000 K
Colour	White
Beam angle	97 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / PMMA
Lamp holder	Plug&Play
Power	30 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver
Outer diameter	230 mm
Built-in diameter	210 mm
Installation depth	70 mm
Current	700 mA
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Circuit type	Series conduction