




BIRO Circle pendant surface luminaire 1.000, direct
Artikel-Nr. 13612173



BIRO Circle pendant surface luminaire 1.000, direct, white, round. Suspended, Ceiling-mounted. Mounting method: Suspended, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 125W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 13.925lm, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13612173
Stand:	18.06.2021 20:34

Type of dimming	DALI	Outer diameter	1 000 mm
Colour	White	Height	100 mm
Colour of light	3000 K	Colour rendering	CRI > 80
System efficiency	111 lm/W	Material	Aluminium / Steel / Plastic
Luminous flux	13,925 lm	Voltage	230V AC 50Hz
Material cover	Plastic, opal	Lamp	LED
Rated life time L80/B50 at 25 °C	50000 h	Light output	Direct
Rated life time L70/B50 at 25 °C	50000 h	Shipping	Incl. converter for connection to the 230-V mains voltage
System output	125 W	Pendulum length max.	5,000 mm
Colour rendering	CRI > 80	Degree of protection	IP40
McAdam-Step	McAdam-Step 3	Protection class	I
Beam angle	116 °	Voltage type	AC
Amount of light sources / fittings	1 Qty		