


BIRO Circle surface luminaire 1.200
Artikel-Nr. 13693173



BIRO Circle surface luminaire 1.200, white, round. Surface mounting, Ceiling-mounted Mounting method: Surface mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP40, Protection class: (EN 61140) I, Voltage: 230V AC 50Hz, Power: 175W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 19.650lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 116°, With control gear: Yes. This luminaire contains incorporated and non-exchangeable LED light sources

Artikel-Nr.	13693173
Stand:	21.07.2021 20:27

control	DALI	Amount of light sources / fittings	1 Qty
Colour	White	Outer diameter	1200 mm
Colour of light	3000 K	Height	100 mm
System efficiency	112 lm/W	Colour rendering	CRI > 80
Luminous flux	19,650 lm	Material	Aluminium / Steel / Plastic
Material cover	Plastic, opal	Voltage	230V AC 50Hz
Rated life time L80/B50 at 25 °C	50000 h	Lamp	LED
Rated life time L70/B50 at 25 °C	50000 h	Light output	Direct
System output	175 W	Shipping	Incl. converter for connection to the 230-V mains voltage
Colour rendering	CRI > 80	Degree of protection	IP40
McAdam-Step	McAdam-Step 3	Protection class	I
Beam angle	116 °	Voltage type	AC