




LED surface-mounted / recessed downlight MOON

Artikel-Nr. 12164023



LED surface-mounted / recessed downlight MOON, chrome, round. In a compact design, for installation in tool-less rapid assembly systems. Lamps optimized for installation in furniture and wood-based materials. This lamp can be used as a recessed (hole cut-out: 56 mm, installation depth: 3.5 mm, mounting height: 2.2 mm), as well as surface-mounted lamp (total height: 5.9 mm) using the supplied mounting housing. Outer edge nickel matte, magnetically attached cover in the color as per the table of products. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Voltage: 12V , Power: 2.6W, Amount of light sources / fittings: 1 Qty, Luminous flux: 180lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 120°, Adjustability: Not adjustable, With control gear: No, control: Dimming depending on driver.

Artikel-Nr.	12164023
Stand:	20.07.2021 14:04

Colour of light	3000 K
Colour	Chrome
Beam angle	120 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Steel / Plastic
Power	2,6 W
Lamp	LED
Shipping	Including 2,000 mm connecting cable
Colour rendering	CRI > 85

control	Dimming depending on driver
Outer diameter	75 mm
Built-in diameter	56 mm
Installation depth	3.5 mm
Voltage	12V
Degree of protection	IP20
Protection class	III
Adjustability	Not adjustable
Height	5.9 mm
Circuit type	Parallel conduction