




LED recessed spot set, phase dimmable
Artikel-Nr. 39261023



LED recessed spot set, phase dimmable, chrome, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Polycarbonate, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 740lm, Colour temperature: 2.700 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39261023
Stand:	25.10.2021 21:31

Colour temperature	2700 K	Outer diameter	82 mm
Colour	Chrome	Built-in diameter	68 mm
Beam angle	38 °	Installation depth	38 mm
Amount of light sources / fittings	1 Qty	Voltage	230V AC 50Hz
Material	Aluminium / Polycarbonate	Degree of protection	IP20
Power	7 W	Protection class	II
Lamp	LED	Adjustability	Pivoted
Colour rendering	CRI > 80	Swivel angle	30 °
Control	Trailing-edge phase	Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.