




LED recessed spot set BB15, phase dimmable incl. connection box

Artikel-Nr. 39475073



LED recessed spot set BB15, phase dimmable incl. connection box, white, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, trailing-edge phase dimmable, dimensions of converter: L 110 x W 50 x H 19 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Degree of protection: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Not adjustable, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	39475073
Stand:	26.10.2021 02:43

Colour temperature	3000 K
Colour	White
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Edelstahl V4A / Aluminium / Glas / Kunststoff
Power	6 W
Lamp	LED
Colour rendering	CRI > 80

Control	Trailing-edge phase
Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	45 mm
Voltage	230V AC 50Hz
Degree of protection	IP54*
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction