



LED recessed spot TUBIC

Artikel-Nr. 13126173



1.0 m	0.7 0.7	1173.2
2.0 m	1.4 1.4	283.3
3.0 m	2.1 2.0	130.4
4.0 m	2.8 2.7	73.3
5.0 m	3.5 3.4	46.9
	Ø (m)	E0(0°) [lx]

LED recessed spot TUBIC, white, round. In a compact design, for installation in tool-less rapid assembly systems Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	13126173
Stand:	25.10.2021 20:59

Colour temperature	3000 K
Colour	White
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	Dimming depending on driver
Outer diameter	80 mm

Built-in diameter	68 mm
Installation depth	50 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Circlip	Without circlip
Adjustability	Pivoted
Aufbauhöhe	20 mm
Swivel angle	25 °
Circuit type	Series conduction