




LED recessed spot, IP65, dim2warm
Artikel-Nr. 12444073



LED recessed spot, IP65, dim2warm, white, round. In a compact design, for installation in tool-less rapid assembly systems. If the lamp is dimmed, the color temperature is reduced. Lamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Steel / Silicone rubber / Plastic, Degree of protection: according to DIN EN 60529 IP65, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 900lm, Colour temperature: from 1.800 K up to 3.000 K, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12444073
Stand:	25.10.2021 22:53

Colour temperature	3000 K - 1800 K	Control	Dimming depending on driver
Colour	White	Outer diameter	82 mm
Beam angle	38 °	Built-in diameter	68 mm
Amount of light sources / fittings	1 Qty	Installation depth	84 mm
Material	Aluminium / Steel / Silicone rubber / Plastic	Current	350 mA
Lamp holder	Plug&Play	Degree of protection	IP65
Power	12 W	Protection class	III
Lamp	LED	Adjustability	Pivoted
Colour rendering	CRI > 90	Swivel angle	30 °
		Circuit type	Series conduction