




LED recessed spot set BB16, DALI dimmable incl. connection box
Artikel-Nr. 41476073



LED recessed spot set BB16, DALI dimmable incl. connection box, white, square. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, DALI-2 dimmable, dimensions of converter: L 130 x W 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium, Degree of protection: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Not adjustable, With control gear: Yes, Control: DALI-2 .

Artikel-Nr.	41476073
Stand:	26.10.2021 02:37
Colour temperature	3000 K
Colour	White
Length	82 mm
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Edelstahl V4A / Aluminium / Glas / Kunststoff
Power	6 W
Lamp	LED
scope of delivery	inkl. Anschlussbox, 5-polig
Colour rendering	CRI > 80
Control	DALI-2
Built-in diameter	68 mm
Installation depth	45 mm
Voltage	230V AC 50Hz
Degree of protection	IP54 *
Protection class	II
Adjustability	Not adjustable
Length	82 mm
Width	82 mm
Circuit type	Parallel conduction

Alle technischen Daten wie Lichttechnische-, Gewichts- und Maßangaben basieren auf Bemessungswerten und sind sorgfältig erstellt. Die mögliche Toleranz der Farbtemperatur beträgt +/- 150K. Die Leistung und Lichtstrom unterliegen initial einer Toleranz von +/- 10%.Die Werte gelten, wenn nicht anders beschrieben, für eine Umgebungstemperatur von 25°C. Technische Änderungen und Irrtümer vorbehalten. Alle Preisangaben verstehen sich als (UVP) in Euro ohne MwSt. Bestellung erfolgt zu unseren Allgemeinen Verkaufsbedingungen unter www.brumberg.com/de/agb/allgemeine-verkaufsbedingungen/.