



LED recessed spot set BB35, DALI dimmable, incl. connection box  
**Artikel-Nr. 4 1479 173**



LED recessed spot set BB35, DALI dimmable, incl. connection box, white, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, DALI-2 dimmable, dimensions of converter: L 130 x W 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 7W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 40°, Adjustability: Pivoted, With control gear: Yes, Control: DALI-2 .

<b>Artikel-Nr.</b>	<b>4 1479 173</b>
<b>Stand:</b>	25.10.2021 23:57

Colour temperature	3000 K
Colour	White
Beam angle	40 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic
Power	7 W
Lamp	LED
Colour rendering	CRI > 80
Control	DALI-2
Outer diameter	82 mm

Built-in diameter	68 mm
Installation depth	38 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Pivoted
Swivel angle	20 °
Circuit type	Parallel conduction
Suitable for through-wiring	Yes