




LED recessed spotlight  
Artikel-Nr. 12590174



LED recessed spotlight, white, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 32W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 4.030lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 30°, Adjustability: Rotable and pivoted, With control gear: Yes.

|                                    |                             |
|------------------------------------|-----------------------------|
| Artikel-Nr.                        | 12590174                    |
| Stand:                             | 19.07.2021 12:32            |
| Colour of light                    | 4000 K                      |
| Colour                             | White                       |
| Beam angle                         | 30 °                        |
| Amount of light sources / fittings | 1 Qty                       |
| Material                           | Aluminium / Glass / Plastic |
| Power                              | 32 W                        |
| Lamp                               | LED                         |
| Colour rendering                   | CRI > 90                    |
| Outer diameter                     | 182 mm                      |
| Built-in diameter                  | 170 mm                      |
| Installation depth                 | 125 mm                      |
| Voltage                            | 230V AC 50Hz                |
| Degree of protection               | IP20                        |
| Protection class                   | II                          |
| Adjustability                      | Rotable and pivoted         |
| Rotation angle                     | 355 °                       |
| Swivel angle                       | 30 °                        |
| Circuit type                       | Parallel conduction         |