


LED recessed spot
Artikel-Nr. 12396074



LED recessed spot, white, round. In a compact design, for installation in tool-less rapid assembly systemsLamp holder: Plug&Play, Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) III, Current: 350 mA, Power: 12W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.280lm, Colour temperature: 4.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: No, Control: Dimming depending on driver.

Artikel-Nr.	12396074
Stand:	26.10.2021 05:35

Colour temperature	4000 K
Colour	White
Rated life time L80/B20 at 25 °C	50000 h
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass
Lamp holder	Plug&Play
Power	12 W
Lamp	LED
Colour rendering	CRI > 80

Control	Dimming depending on driver
Outer diameter	110 mm
Built-in diameter	95 mm
Installation depth	60 mm
Current	350 mA
Degree of protection	IP20
Protection class	III
Adjustability	Pivoted
Swivel angle	15 °
Circuit type	Series conduction