




LED-Einbaustrahler, DALI dimmbar,
mit Anschlussbox



LED-Einbaustrahler, DALI dimmbar, mit Anschlussbox, chrome, square. In a compact design, for installation in tool-less rapid assembly systems. Set inkl. Konverter für 230 V-Netzspannung, DALI-2 dimmbar, Maße Konverter: L 130 x B 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: DALI-2 .

Artikel-Nr.	41444073
Stand:	26.10.2021 03:57
Colour temperature	3000 K
Colour	Chrome
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	6 W
Lamp	LED
scope of delivery	inkl. Anschlussbox, 5-polig
Colour rendering	CRI > 80
Control	DALI-2
Built-in diameter	68 mm
Installation depth	50 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Circlip	Without circlip
Adjustability	Pivoted
Swivel angle	20 °
Circuit type	Parallel conduction