



LED-Einbaudownlight, DALI dimmbar  
**Artikel-Nr. 12552174**



1.0 m	1.5	1237.3
2.0 m	3.0	309.3
3.0 m	4.5	137.5
4.0 m	6.0	77.3
5.0 m	7.5	49.5
Ø (m)		E0(0°) [lx]

LED-Einbaudownlight, DALI dimmbar, white, round. In a compact design, for installation in tool-less rapid assembly systems  
 Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 25W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.962lm, Colour temperature: 4.000 K, Light colour : White, Beam angle: 74°, Adjustability: Not adjustable, With control gear: Yes, Control: DALI.

<b>Artikel-Nr.</b>	<b>12552174</b>
<b>Stand:</b>	26.10.2021 05:03

Colour temperature	4000 K
Colour	White
Beam angle	74 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Plastic / Steel
Power	25 W
Lamp	LED
scope of delivery	inkl. Konverter zum Anschluss an 230 V-Netzspannung, DALI dimmbar
Colour rendering	CRI > 90

Glare evaluation	UGR < 22
Control	DALI
Outer diameter	204 mm
Built-in diameter	190 mm
Installation depth	102 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction