




LED recessed downlight  
Artikel-Nr. 12572174



LED recessed downlight, white, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic / Steel, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 19W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 1.310lm, Colour temperature: 4000 K, Light colour : White, Beam angle: 68°, Adjustability: Not adjustable, With control gear: Yes.

|             |                  |
|-------------|------------------|
| Artikel-Nr. | 12572174         |
| Stand:      | 19.07.2021 09:30 |

|                                    |                             |
|------------------------------------|-----------------------------|
| Colour of light                    | 4000 K                      |
| Colour                             | White                       |
| Beam angle                         | 68 °                        |
| Amount of light sources / fittings | 1 Qty                       |
| Material                           | Aluminium / Plastic / Steel |
| Power                              | 19 W                        |
| Lamp                               | LED                         |
| Colour rendering                   | CRI > 90                    |
| Glare evaluation                   | UGR < 22                    |

|                      |                     |
|----------------------|---------------------|
| control              |                     |
| Outer diameter       | 180 mm              |
| Built-in diameter    | 165 mm              |
| Installation depth   | 90 mm               |
| Voltage              | 230V AC 50Hz        |
| Degree of protection | IP20                |
| Protection class     | II                  |
| Adjustability        | Not adjustable      |
| Circuit type         | Parallel conduction |