


LED recessed downlight, DALI dimmable
Artikel-Nr. 41552074



LED recessed downlight, DALI dimmable, round. In a compact design, for installation in tool-less rapid assembly systems
Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 20W, Amount of light sources / fittings: 1.0 Qty, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: Yes, control: DALI.

Artikel-Nr.	41552074		
Stand:	06.09.2021 13:30		
Colour temperature	4000 K	Control	DALI
Beam angle	40 °	Outer diameter	130 mm
Amount of light sources / fittings	1 Qty	Built-in diameter	115 mm
Material	Aluminium / Glass / Plastic	Installation depth	60 mm
Lamp	LED	Voltage	230V AC 50Hz
Shipping	Incl. converter for connection to 230 V mains voltage, DALI-2 dimmable and connection box	Degree of protection	IP20
Colour rendering	CRI > 80	Protection class	II
Glare evaluation	UGR < 19	Adjustability	Not adjustable
		Circuit type	Parallel conduction
		Suitable for through-wiring	Yes