


LED recessed downlight, on/off
Artikel-Nr. 41542074



LED recessed downlight, on/off, round. In a compact design, for installation in tool-less rapid assembly systems Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 20W, Amount of light sources / fittings: 1.0 Qty, Light colour : White, Beam angle: 40°, Adjustability: Not adjustable, With control gear: Yes, control: on/off.

Artikel-Nr.	41542074
Stand:	06.09.2021 13:36

Colour temperature	4000 K
Beam angle	40 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Lamp	LED
Shipping	Incl. converter for connection to 230 V mains voltage, switchable and connection box
Colour rendering	CRI > 80
Glare evaluation	UGR < 19

Control	on/off
Outer diameter	130 mm
Built-in diameter	115 mm
Installation depth	60 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction
Suitable for through-wiring	Yes