



LED recessed downlight set BB15, V4A, IP54, phase dimmable (round converter)



LED recessed downlight set BB15, V4A, IP54, phase dimmable (round converter), stainless steel, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a round converter for 230-V mains voltage, trailing-edge phase, dimensions of converter: D 51 x H 24 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Stainless steel, Degree of protection: according to DIN EN 60529 IP54*, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 680lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Not adjustable, With control gear: Yes, Control: Trailing-edge phase.

Artikel-Nr.	40375423
Stand:	25.10.2021 20:13
Colour temperature	3000 K
Colour	Stainless steel
Beam angle	38 °
Amount of light sources / fittings	1 Qty
Material	Edelstahl V4A / Aluminium / Glas / Kunststoff
Power	6 W
Lamp	LED
Colour rendering	CRI > 80
Control	Trailing-edge phase
Outer diameter	82 mm
Built-in diameter	68 mm
Installation depth	45 mm
Voltage	230V AC 50Hz
Degree of protection	IP54 *
Protection class	II
Adjustability	Not adjustable
Circuit type	Parallel conduction