




LED recessed spot set BB03, DALI dimmable, incl. connection box
Artikel-Nr. 41463153



LED recessed spot set BB03, DALI dimmable, incl. connection box, nickel, round. In a compact design, for installation in tool-less rapid assembly systems. Set including a converter for 230-V mains voltage, DALI-2 dimmable, dimensions of converter: L 130 x W 42 x H 22 mm. Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 6W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 640lm, Colour temperature: 3.000 K, Light colour : White, Beam angle: 38°, Adjustability: Pivoted, With control gear: Yes, Control: DALI-2 .

Artikel-Nr.	41463153
Stand:	25.10.2021 23:37

Colour temperature	3000 K	Outer diameter	82 mm
Colour	Nickel	Built-in diameter	68 mm
Beam angle	38 °	Installation depth	36 mm
Amount of light sources / fittings	1 Qty	Voltage	230V AC 50Hz
Material	Aluminium / Plastic	Degree of protection	IP20
Power	6 W	Protection class	II
Lamp	LED	Adjustability	Pivoted
scope of delivery	Incl. 5-pole connection box	Swivel angle	30 °
Colour rendering	CRI > 80	Circuit type	Parallel conduction
Control	DALI-2	Suitable for through-wiring	Yes