




LED recessed spotlight, cardanic
Artikel-Nr. 12581183



LED recessed spotlight, cardanic, black, square. In a compact design, for installation in tool-less rapid assembly systems
Mounting method: Recessed mounting, Place of installation: Ceiling-mounted, Material: Aluminium / Glass / Plastic, Degree of protection: according to DIN EN 60529 IP20, Protection class: (EN 61140) II, Voltage: 230V AC 50Hz, Power: 40W, Amount of light sources / fittings: 1.0 Qty, Luminous flux: 4.300lm, Colour temperature: 3000 K, Light colour : White, Beam angle: 30°, Adjustability: Rotable and pivoted, With control gear: Yes.

Artikel-Nr.	12581183
Stand:	20.07.2021 06:17
Colour of light	3000 K
Colour	Black
Beam angle	30 °
Amount of light sources / fittings	1 Qty
Material	Aluminium / Glass / Plastic
Power	40 W
Lamp	LED
Colour rendering	CRI > 90
Built-in width	175 mm
Built-in length	175 mm
Installation depth	147 mm
Voltage	230V AC 50Hz
Degree of protection	IP20
Protection class	II
Adjustability	Rotable and pivoted
Length	185 mm
Width	185 mm
Rotation angle	355 °
Swivel angle	30 °
Circuit type	Parallel conduction